

M-POWER-3T

MORMAX

Mormax Company, Inc.

Flmsford, NY 10523

914-699-0101

8 Westchester Plaza



sales@mormax.com mormax com

M-POWER-3TW-AUC-WAB

AC POWER & DATA CONNECTIVITY SOLUTION

Metro Light & Power's line of power & data solutions offers sophisticated design elements combined with greater ease of installation. Streamlined and low-profile, enhanced by side-exiting cords, our outlets advance the industry with their cutting-edge look and feel. We believe flexibility is key, and we provide a variety of mounting options, including the ability to mount in limited spaces. Our outlets are available in many finishes and configurations, in addition to a custom color and finish capability for our clients.

Bezel Finish:

WHITE (ABS)

Custom Finishes Available

M-POWER-3TW-AUC-WAB



Features:

Module/Port Options:

- A Tamper Resistant AC Receptacle
- B Double USB (Fast Charging Ports Rated for 3.2A)
- C HDMI
- D CAT 6
- E 3.5mm Mini Stereo Jack
- F Single USB (Fast Charging Port Rated for 3.2A)
- G RJ 12
- H Switched AC
- 3-Way Switch
- J USB C (High Speed Charging Port)
- K Switched AC (Rocker Switch)

Plug:

Low Profile Flat 45° Angle 120 VAC Plug Standard Straight 120 VAC Plug

- CLEAN, COMPACT DESIGN
- STREAMLINED
- LOW PROFILE
- SIDE-EXITING CORDS
- PLUG & PLAY
- 3.2A HIGH SPEED USB CHARGING FOR ALL DEVICES
- 6' AC CORD & PLUG (FLAT PLUG STANDARD)
- CUSTOMIZABLE CONFIGURATIONS AND FINISHES
- UL LISTED FOR MOUNTING IN FURNITURE
- 15A





M-POWER-3T

MORMAX

Mormax Company, Inc.

8 Westchester Plaza Elmsford, NY 10523

914-699-0101 sales@mormax.com

mormax.com

AC POWER & DATA CONNECTIVITY SOLUTION

M-POWER-3TW-AUC-WAB

Specs:

Modules/Ports:

- Tamper Resistant AC Receptacle
- Double USB (Fast Charging Ports Rated for 3.2A)
- USB C (High Speed Charging Port)

TOP 1.381" (35.082mm) 2.106" (53.503mm) 4 Shown with 1 Tamper Resistant AC, a1 Double USB Charging Port, and 1 USB C Charging Port. 5.570" (141.500mm) 6.319" (160.503mm) 3.861" (98.082mm) 0.619" (15.746mm) 1.233" (31.340mm) 0.613" (15.594mm) D 1.132" (28.766mm) 1.381" (35.082mm) 0.234" (5.944mm) 1 0.118" (3.000mm)



