

# M-POWER-4T

## **AC POWER & DATA CONNECTIVITY SOLUTION**

4T-AAAU-B2ATP

Distributed by



Mormax Company, Inc.

8 Westchester Plaza Flmsford, NY 10523 sales@mormax.com

mormax.com


Metro Light & Power's line of power & data solutions offers sophisticated design elements combined with greater ease of installation. Streamlined and low-profile, enhanced by side-exiting cords, our outlets advance the industry with their cutting-edge look and feel. We believe flexibility is key, and we provide a variety of mounting options, including the ability to mount in limited spaces. Our outlets are available in many finishes and configurations, in addition to a custom color and finish capability for our clients.

Trim Plate Finish:

**SATIN BLACK (ABS)** 

Custom Finishes Available

M-POWER-4T-AAAU-B2ATP



### Features:

#### **Module/Port Options:**

- A Tamper Resistant AC Receptacle
- B USB-A & USB-C (3.0A USB-A / 15W USB-C)
- U Double USB (Fast Charging Ports Rated for 3.2A)
- H HDMI
- 6 CAT 6
- 12 RJ 12
- X Switched AC
- Y 3-Way Switch
- C USB-C (27W High Speed Charging Port)
- Z USB-C (18W High Speed Charging Port)
- R Switched AC (Rocker Switch)

#### Plug:

Supplied with Low Profile Flat 45° Angle 120 VAC Plug Optional Standard Straight 120 VAC Plug Optional Straight 120 VAC Pass-through Plug Shown in Satin Black (ABS) Plate, featuring 3 Tamper Resistant ACs, and 1 Double USB-A Charging Port.

- CLEAN, COMPACT DESIGN
- STREAMLINED
- LOW PROFILE
- SIDE-EXITING CORDS
- PLUG & PLAY
- 3.2A HIGH SPEED USB CHARGING FOR ALL DEVICES
- 6' AC CORD & PLUG (FLAT PLUG STANDARD)
- CUSTOMIZABLE CONFIGURATIONS AND FINISHES
- UL LISTED FOR MOUNTING IN FURNITURE
- 15A






Mormax Company, Inc.

914-699-0101 sales@mormax.com

mormax.com

8 Westchester Plaza Elmsford, NY 10523

TOP Specs: **Modules/Ports:** 2.000" (50.800mm) Tamper Resistant AC Receptacle Double USB (Fast Charging Ports - Rated for 3.2A) 2.106" (53.503mm) 7.240" (183.903mm) 7.559" (192.003mm) Shown with 3 Tamper Resistant ACs, and 1 Double USB-A Charging Port. Optional Straight 120 VAC Pass-through Plug 0.619" (15.746mm) 1.233" (31.340mm) 1.141" 0.984 (25.00mr 0.613" (15.594mm) 1.704" (43.300mm) Ø 1.132" (63.900mm) 2.000" (50.800mm) 0.093" (2.381mm) 0.140" (3.563mm) 0.234" (5.944mm) 0.118" (3.000mm) 1



SIDE 0.905" (23.000mm)